



内外倒角 ID and OD chamfers

S ₃	C _o	C _i	β
0.75	0.5±0.3	0.25±0.2	35°±5°
1.00	0.6±0.3	0.30±0.2	35°±5°
1.50	0.7±0.3	0.50±0.3	35°±5°

S ₃	C _o	C _i	β
2.00	1.2±0.4	0.50±0.3	35°±5°
2.50	1.8±0.6	0.60±0.3	45°±5°

单位Unit: mm

5120 Bronze Sleeve Bushing Specification & Tolerance
5120 青铜轴套规格及公差

内径 D _i φd	10	12	14	15	16	18	20	22	24	25	28	30	32	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115		
外径 D _o φD	12	14	16	17	18	20	23	25	27	28	31	34	36	39	44	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120		
10	●	●	●	●	●	●	●	●																								
15	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●																	
20	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●															
25			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●														
30							●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
35												●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
40												●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
50															●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
60																●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
70																		●	●	●	●	●	●	●	●	●	●	●	●	●	●	
80																				●	●	●	●	●	●	●	●	●	●	●	●	
90																									●	●	●	●	●	●	●	●
100																											●	●	●	●	●	●

5120 Bronze Sleeve Bushing Specification & Tolerance
5120 青铜轴套规格及公差

内径 D _i φd	120	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	225	230	240	250	260	270	280	290	300	
外径 D _o φD	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	220	230	235	245	255	265	275	285	295	305		
25																														
30																														
35																														
40																														
50																														
60	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
90	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
100	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

Order 订购 . . .
 5120 . 020 . 023 . 020